




Vulcan Engineering Group

Vulcan Expanded PTFE Sealants

Significantly Reduce Inventories & Costs Whilst Maximising Gasket Performance! TEFCAN is 100% PURE Expanded PTFE, available as Sheet, Gasket Tape and Joint Sealants, in a flexible form that compresses to perform a gas tight seal.

-  FDA compliant material.
-  Takes up surface irregularities.
-  Non contaminating, non toxic.
-  Easy to cut, install and remove.
-  Highly compressible and pliable.
-  Forms a tight, structurally stable seal.
-  Forms a seal with low clamping force.
-  Incredibly resistant to creep, relaxation and cold flow, unlike virgin PTFE.
-  pH 0 –14, except for molten alkali metals and elemental fluorine.
-  Service limits: - 240°C to 310°C. Full vacuum to 3000 psi.
-  Seals almost any static application.
-  Impervious to gases and liquids.
-  High tensile strength.



Assured quality performance, at highly competitive pricing, backed by Vulcan's electronic stock supply service.



The Vulcan Engineering Group, The Southwest Centre, Troutbeck Road, Sheffield,
S8 0JR, UK. Tel: +44 (0) 114 249 3333,
e-mail: service@vulcan-eng.com Web Site: www.vulcan-eng.com

Document Ref: TEFFLY
Revision: 1
Created By: LDS/OC
Authorisation: OC
Date Created: 21/11/2013
Revision Date: 23/01/2014